

Poly Spill Pallets

The poly spill pallet is actually a spill-proof plastic pallet with sump and forklift groove. It can be used for storing, handling and transferring oil drums and chemical drums. All liquid leaking out will flow into the sump rather than the ground. With the supporting ramp, chemical drums can be handled easily and quickly. The high-strength mobile and removable grate is easy to remove, clean and replace. Liquid in the sump can be discharged through the leakage holes, and most of liquid can be recycled.

SPP102H



SPP102

SPP104

Poly Spill Pallets

Product	200L Drum Quantity	Capacity (Gal/L)	Loading Capacity (Kgs.)	Ext. Dimensions (H×L×W/cm)	Forklift Operation	Model
Spill Pallet Poly Spill Pallet(2 Drum)	2	32/120	1500	30×130×66	Bidirectional operation	SPP102
Spill Pallet Poly Spill Pallet(2 Drum)	2	58/220	2000	45×131×67	Bidirectional operation	SPP102H
Spill Pallet Poly Spill Pallet(4 Drum)	4	68/260	3000	30×130×128	Quadridirectional operation	SPP104

Poly Spill Decks

The poly spill deck is lower than the pallet, thus saving the space, improving the safety, efficiency and facilitating handling of oil drums and chemical drums. Generally, the poly spill deck is used for storing oil drums, chemical drums, etc., instead of transferring such containers. When installed in a workshop, the spill deck can be used for various operations (oil extracting, filling and separating, etc.), as a platform. It is also equipped with the same grate and drain holes. Various decks can be assembled to form a stable and reliable workstation.



SPP101

SPP401

SPP103

Poly Spill Decks

Product	200L Drum Quantity	Capacity (Gal/L)	Loading Capacity (Kgs.)	Ext. Dimensions (H×L×W/cm)	Forklift Operation	Model
Spill Deck Poly Spill Deck(Single Drum)	1	11/42	600	15×66×66	NA	SPP401
Spill Deck Poly Spill Deck(2 Drum)	2	21/80	1500	15×130×66	NA	SPP101
Spill Deck Poly Spill Deck(4 Drum)	4	40/150	2500	15×130×128	NA	SPP103

Steel Spill Pallets

The steel spill pallet can also be used for storing, handling and separating oil drums and chemical drums. It is made of 3mm hot-rolled steel plate, stable and durable. The pallet body is coated with epoxy resin powder, forming a bright, dust-proof, rust-proof and moisture-proof surface. The fiberglass-reinforced grate of light weight, high strength, wear resistance and aging resistance can be removed for easy cleaning. The pallet can meet the handling needs of various forklifts. The cart type two-drum pallet, with large sump capacity, is more convenient to operate. It is designed in accordance with the leakage containing standards, and has passed the 100% leakage containing test. With the drum bracket at the pallet center, the load can be distributed, thus achieving higher performance. The 3/4"NPT (hex) ball valve in standard configuration is installed in the leakage hole in order to transfer the leaking liquid and facilitate the operation. The user is allowed to remove the bottom plug to fully discharge liquid and clean the pallet.



SPM202

SPM222

SPM204

SPM112